

Enquiry form for globe valves / valves / gate valves

Process data:	(in case of availability)	Manufacturer	Serial number	
Medium / Density:	_____	_____	_____	
Max. Temperature:	_____			
Upstream pressure P1:	_____			
Holding pressure P2:	_____			
Flow rate:	min. _____	max. _____		
Kvs value	_____	<input type="checkbox"/> =% <input type="checkbox"/> linear	<input type="checkbox"/> _____	
Documentation / authorisations:	<input type="checkbox"/> TA-air Further approvals	<input type="checkbox"/> AD 2000 <input type="checkbox"/> _____	<input type="checkbox"/> _____	
Further information	_____			
VALVE				
Flange standard	<input type="checkbox"/> EN 1092-1/2	<input type="checkbox"/> ANSI	<input type="checkbox"/> _____	
Nominal size	<input type="checkbox"/> DN _____	<input type="checkbox"/> Inch _____		
Flange connection	<input type="checkbox"/> PN _____	<input type="checkbox"/> Class _____		
Connection type	<input type="checkbox"/> Flange	<input type="checkbox"/> Thread	<input type="checkbox"/> Socket	<input type="checkbox"/> Foodstuffs
Design	<input type="checkbox"/> Intermediate Flange	<input type="checkbox"/> Flange LUG type	<input type="checkbox"/> Double Flange	
	<input type="checkbox"/> 2-way	<input type="checkbox"/> 3-way	<input type="checkbox"/> 4-way	
	<input type="checkbox"/> Bottom outlet valve	<input type="checkbox"/> Angle valve	<input type="checkbox"/> _____	
	<input type="checkbox"/> Insulating part	<input type="checkbox"/> Bellows	<input type="checkbox"/> _____	
	<input type="checkbox"/> TA-air	<input type="checkbox"/> AD 2000	<input type="checkbox"/> _____	
Function	<input type="checkbox"/> Shut-off	<input type="checkbox"/> Control		
Body material	<input type="checkbox"/> _____			
Shut-off device material	<input type="checkbox"/> _____			
Lining	<input type="checkbox"/> _____			
Overall length in mm	<input type="checkbox"/> _____			
Actuation:	<input type="checkbox"/> Free shaft end	<input type="checkbox"/> Handwheel	<input type="checkbox"/> Pneumatic	<input type="checkbox"/> Electric
Electronical actuator	Brand: <input type="checkbox"/> _____	<input type="checkbox"/> 220 – 240V AC	<input type="checkbox"/> 380 – 460V DS	<input type="checkbox"/> 24V DC
	Nominal voltage:	Additional function: <input type="checkbox"/> _____		
Pneumatic actuator	<input type="checkbox"/> Single-acting	<input type="checkbox"/> Double-acting	<input type="checkbox"/> Spring-opening	<input type="checkbox"/> Spring-closing
	Supply air pressure:	<input type="checkbox"/> _____ bar		
Drive accessories:				
Solenoid valve:	<input type="checkbox"/> 3/2 way valve	<input type="checkbox"/> 5/2 way valve		
Manufacturer	<input type="checkbox"/> _____			
Control voltage	<input type="checkbox"/> 24V DC	<input type="checkbox"/> 230V/50Hz AC	<input type="checkbox"/> _____	
Limit switch:	<input type="checkbox"/> Inductiv	<input type="checkbox"/> Microswitch	<input type="checkbox"/> _____	<input type="checkbox"/> Ex version
Positioner:				
Input signal:	<input type="checkbox"/> 4-20 mA	<input type="checkbox"/> 0-10V		

Analogue feedback: yes no

GATE VALVE

Flange standard	<input type="checkbox"/> EN 1092-1/2	<input type="checkbox"/> ANSI	<input type="checkbox"/> _____	
Nominal size	<input type="checkbox"/> DN _____	<input type="checkbox"/> Inch _____		
Flange connection	<input type="checkbox"/> PN _____	<input type="checkbox"/> Class _____		
Connection type	<input type="checkbox"/> Flansch	<input type="checkbox"/> Gewinde	<input type="checkbox"/> Muffe	<input type="checkbox"/> Lebensmittel
Design	<input type="checkbox"/> Intermediate Flange	<input type="checkbox"/> Flange LUG type	<input type="checkbox"/> Double Flange	
	<input type="checkbox"/> 2-way	<input type="checkbox"/> 3-way	<input type="checkbox"/> 4-way	
	<input type="checkbox"/> Bottom outlet valve	<input type="checkbox"/> Angle valve	<input type="checkbox"/> _____	
	<input type="checkbox"/> Insulating part	<input type="checkbox"/> Bellows	<input type="checkbox"/> _____	
	<input type="checkbox"/> TA-air	<input type="checkbox"/> AD 2000	<input type="checkbox"/> _____	
Function	<input type="checkbox"/> Shut-off	<input type="checkbox"/> Control		
Body material	<input type="checkbox"/> _____			
Shut-off device material	<input type="checkbox"/> _____			
Lining	<input type="checkbox"/> _____			
Overall length in mm	<input type="checkbox"/> _____			
Actuation:	<input type="checkbox"/> Free shaft end	<input type="checkbox"/> Handwheel	<input type="checkbox"/> Pneumatic	<input type="checkbox"/> Electric
Electronical actuator	Brand:	<input type="checkbox"/> _____		
	Nominal voltage:	<input type="checkbox"/> 220 – 240V AC	<input type="checkbox"/> 380 – 460V DS	<input type="checkbox"/> 24V DC
	Additional function:	<input type="checkbox"/> _____		
Pneumatic actuator	<input type="checkbox"/> Single-acting	<input type="checkbox"/> Double-acting	<input type="checkbox"/> Spring-opening	<input type="checkbox"/> Spring-closing
	Supply air pressure:	<input type="checkbox"/> _____ bar		
Actuator accessories:				
Solenoid valve:	<input type="checkbox"/> 3/2 way valve	<input type="checkbox"/> 5/2 way valve		
Manufacturer	<input type="checkbox"/> _____			
Control voltage	<input type="checkbox"/> 24V DC	<input type="checkbox"/> 230V/50Hz AC	<input type="checkbox"/> _____	
Limit switch:	<input type="checkbox"/> Inductiv	<input type="checkbox"/> Microswitch	<input type="checkbox"/> _____	<input type="checkbox"/> Ex version
Positioner:				
Input signal:	<input type="checkbox"/> 4-20 mA	<input type="checkbox"/> 0-10V		
Analogue feedback:	<input type="checkbox"/> yes	<input type="checkbox"/> no		

WEDGE GATE VALVE

Flange standard	<input type="checkbox"/> EN 1092-1/2	<input type="checkbox"/> ANSI	<input type="checkbox"/> _____	
Nominal size	<input type="checkbox"/> DN _____	<input type="checkbox"/> Inch _____		
Flange connection	<input type="checkbox"/> PN _____	<input type="checkbox"/> Class _____		
Connection type	<input type="checkbox"/> Flange	<input type="checkbox"/> Thread	<input type="checkbox"/> Socket	<input type="checkbox"/> Foodstuffs
Bauweise	<input type="checkbox"/> Intermediate Flange	<input type="checkbox"/> Flange LUG type	<input type="checkbox"/> Double Flange	
	<input type="checkbox"/> 2-way	<input type="checkbox"/> 3-way	<input type="checkbox"/> 4-way	
	<input type="checkbox"/> Bottom outlet valve	<input type="checkbox"/> Angle valve	<input type="checkbox"/> _____	
	<input type="checkbox"/> Insulating part	<input type="checkbox"/> Bellows	<input type="checkbox"/> _____	
	<input type="checkbox"/> TA-air	<input type="checkbox"/> AD 2000	<input type="checkbox"/> _____	
Function	<input type="checkbox"/> Shut-off	<input type="checkbox"/> Control		
Body material	<input type="checkbox"/> _____			
Shut-off device material	<input type="checkbox"/> _____			
Lining	<input type="checkbox"/> _____			
Overall length in mm	<input type="checkbox"/> _____			
Actuation:	<input type="checkbox"/> Free shaft end	<input type="checkbox"/> Handwheel	<input type="checkbox"/> Pneumatic	<input type="checkbox"/> Electric
Electronical actuator	Brand:	<input type="checkbox"/> _____		
	Nominal voltage:	<input type="checkbox"/> 220 – 240V AC	<input type="checkbox"/> 380 – 460V DS	<input type="checkbox"/> 24V DC
	Additional function:	<input type="checkbox"/> _____		
Pneumatic actuator	<input type="checkbox"/> Single-acting	<input type="checkbox"/> Double-acting	<input type="checkbox"/> Spring-opening	<input type="checkbox"/> Spring-closing
	Supply air pressure:	<input type="checkbox"/> _____ bar		
Actuator accessories:				
Solenoid valve:	<input type="checkbox"/> 3/2 way valve	<input type="checkbox"/> 5/2 way valve		
Manufacturer	<input type="checkbox"/> _____			
Control voltage	<input type="checkbox"/> 24V DC	<input type="checkbox"/> 230V/50Hz AC	<input type="checkbox"/> _____	
Limit switch:	<input type="checkbox"/> Inductiv	<input type="checkbox"/> Microswitch	<input type="checkbox"/> _____	<input type="checkbox"/> Ex version
Positioner:				
Input signal:	<input type="checkbox"/> 4-20 mA	<input type="checkbox"/> 0-10V		
Analogue feedback:	<input type="checkbox"/> yes	<input type="checkbox"/> no		