

Enquiry form for rotary valves

Process data:

Medium / Density: _____
 Max. Temperature: _____
 Upstream pressure P1: _____
 Holding pressure P2: _____
 Flow rate: min. _____ max. _____
 Kvs-value: _____

(In case of
availability)

Manufacturer

Serialnummer

Documentations /
authorisations: TA-air
Further approvals

AD 2000

Further information _____

BUTTERFLY VALVE

Flange standard EN 1092-1/2 ANSI _____
 Nominal size DN _____ Inch _____
 Flange connection PN _____ Class _____
 Connection type Flange Thread Socket Foodstuffs
 Design Intermediate Flange Flange LUG type Double flange
 2-way **3-way** **4-way**
 Bottom outlet valve Angle valve _____
 Insulating part Bellows _____
 TA-air AD 2000 _____

Function Shut-off Control
 Body material _____
 Shut-off device mat. _____
 Lining _____
Overall length in mm _____

Actuation: Free shaft end Handwheel Pneumatic Electric

Electrical actuator Brand: _____
 Nominal Voltage: 220 – 240V AC 380 – 460V DS 24V DC
 Additional function: _____

Pneumatic actuator: single-acting double-acting spring-opening spring-closing
 Supply air pressure: _____ bar

Actuator accessoires:

Solenoid valve: 3/2 way valve 5/2 way valve
 Manufacturer _____
 Control voltage 24V DC 230V/50Hz AC _____

Limit switch: Inductiv Microswitch _____ Ex version

Positioner:
 Input signal: 4-20 mA 0-10V

Analogue feedback
 signal: yes no

BALL VALVE/ PLUG VALVE

Flange standard	<input type="checkbox"/> EN 1092-1/2	<input type="checkbox"/> ANSI	<input type="checkbox"/> _____	
Nominal size	<input type="checkbox"/> DN _____	<input type="checkbox"/> Inch _____		
Flange connection	<input type="checkbox"/> PN _____	<input type="checkbox"/> Class _____		
Connection type	<input type="checkbox"/> Flange	<input type="checkbox"/> Thread	<input type="checkbox"/> Socket	<input type="checkbox"/> Foodstuffs
Design	<input type="checkbox"/> Intermediate Flange	<input type="checkbox"/> Flange LUG type	<input type="checkbox"/> Double Flange	
	<input type="checkbox"/> 2-way	<input type="checkbox"/> 3-way	<input type="checkbox"/> 4-way	
	<input type="checkbox"/> Bottom outlet valve	<input type="checkbox"/> Angle valve	<input type="checkbox"/> _____	
	<input type="checkbox"/> Insulating part	<input type="checkbox"/> Bellows	<input type="checkbox"/> _____	
	<input type="checkbox"/> TA-air	<input type="checkbox"/> AD 2000	<input type="checkbox"/> _____	
Function	<input type="checkbox"/> Shut-off	<input type="checkbox"/> Control		
Body material	<input type="checkbox"/> _____			
Shut-off device material	<input type="checkbox"/> _____			
Lining	<input type="checkbox"/> _____			
Overall length in mm	<input type="checkbox"/> _____			
Actuation:	<input type="checkbox"/> Free shaft end	<input type="checkbox"/> Handwheel	<input type="checkbox"/> Pneumatic	<input type="checkbox"/> Electric
Electrical actuator	Brand:	<input type="checkbox"/> _____		
	Nominal voltage:	<input type="checkbox"/> 220 – 240V AC	<input type="checkbox"/> 380 – 460V DS	<input type="checkbox"/> 24V DC
	Additional function:	<input type="checkbox"/> _____		
Pneumatic actuator	<input type="checkbox"/> Single-acting	<input type="checkbox"/> Double-acting	<input type="checkbox"/> Spring-opening	<input type="checkbox"/> Spring-closing
	Supply air pressure:	<input type="checkbox"/> _____ bar		
Actuator accessoires:				
Solenoid valve:	<input type="checkbox"/> 3/2 way valve	<input type="checkbox"/> 5/2 way valve		
Manufacturer	<input type="checkbox"/> _____			
Control voltage	<input type="checkbox"/> 24V DC	<input type="checkbox"/> 230V/50Hz AC	<input type="checkbox"/> _____	
Limit switch:	<input type="checkbox"/> Inductive	<input type="checkbox"/> Microswitch	<input type="checkbox"/> _____	<input type="checkbox"/> Ex version
Positoner:				
Input signal:	<input type="checkbox"/> 4-20 mA	<input type="checkbox"/> 0-10V		
Analogue feedback signal:	<input type="checkbox"/> yes	<input type="checkbox"/> no		

BALL SECTOR VALVE

Flange standard	<input type="checkbox"/> EN 1092-1/2	<input type="checkbox"/> ANSI	<input type="checkbox"/> _____
Nominal size	<input type="checkbox"/> DN _____	<input type="checkbox"/> Inch _____	
Flange connection	<input type="checkbox"/> PN _____	<input type="checkbox"/> Class _____	
Connection type	<input type="checkbox"/> Flange	<input type="checkbox"/> Thread	<input type="checkbox"/> Socket <input type="checkbox"/> Foodstuffs
Design	<input type="checkbox"/> Intermediate Flange	<input type="checkbox"/> Flange LUG type	<input type="checkbox"/> Double Flange
	<input type="checkbox"/> 2-way	<input type="checkbox"/> 3-way	<input type="checkbox"/> 4-way
	<input type="checkbox"/> Bottom outlet valve	<input type="checkbox"/> Angle valve	<input type="checkbox"/> _____
	<input type="checkbox"/> Insulating part	<input type="checkbox"/> Bellwos	<input type="checkbox"/> _____
	<input type="checkbox"/> TA-air	<input type="checkbox"/> AD 2000	<input type="checkbox"/> _____
Function	<input type="checkbox"/> Shut-Off	<input type="checkbox"/> Control	
Body material	<input type="checkbox"/> _____		
Shut-off device material	<input type="checkbox"/> _____		
Lining	<input type="checkbox"/> _____		
Overall length in mm	<input type="checkbox"/> _____		
Actuation:	<input type="checkbox"/> Free shaft end	<input type="checkbox"/> Handwheel	<input type="checkbox"/> Pneumatic <input type="checkbox"/> Electric
Electronical actuator	Brand: <input type="checkbox"/> _____		
	Nominal voltage: <input type="checkbox"/> 220 – 240V AC	<input type="checkbox"/> 380 – 460V DS	<input type="checkbox"/> 24V DC
	Additional function: <input type="checkbox"/> _____		
Pneumatic actuator	<input type="checkbox"/> Single-acting	<input type="checkbox"/> Double-acting	<input type="checkbox"/> Spring-opening <input type="checkbox"/> Spring-closing
	Supply air pressure: <input type="checkbox"/> _____ bar		
Drive accessoires:			
Solenoid valve:	<input type="checkbox"/> 3/2 way valve	<input type="checkbox"/> 5/2 way valve	
Manufacturer	<input type="checkbox"/> _____		
Control voltage	<input type="checkbox"/> 24V DC	<input type="checkbox"/> 230V/50Hz AC	<input type="checkbox"/> _____
Limit switch:	<input type="checkbox"/> Inductiv	<input type="checkbox"/> Microswitch	<input type="checkbox"/> _____ <input type="checkbox"/> Ex version
Positioner:			
Input signal:	<input type="checkbox"/> 4-20 mA	<input type="checkbox"/> 0-10V	
Analogue feedback:	<input type="checkbox"/> yes	<input type="checkbox"/> no	

ROTARY PLUG VALVE

Flange standard	<input type="checkbox"/> EN 1092-1/2	<input type="checkbox"/> ANSI	<input type="checkbox"/>	
Nominal size	<input type="checkbox"/> DN _____	<input type="checkbox"/> Inch _____		
Flange connection	<input type="checkbox"/> PN _____	<input type="checkbox"/> Class _____		
Connection type	<input type="checkbox"/> Flange	<input type="checkbox"/> Thread	<input type="checkbox"/> Socket	<input type="checkbox"/> Foodstuffs
Design	<input type="checkbox"/> Intermediate Flange	<input type="checkbox"/> Flange LUG type	<input type="checkbox"/> Double Flange	
	<input type="checkbox"/> 2-way	<input type="checkbox"/> 3-way	<input type="checkbox"/> 4-way	
	<input type="checkbox"/> Bottom outlet valve	<input type="checkbox"/> Angle valve	<input type="checkbox"/> _____	
	<input type="checkbox"/> Insulating part	<input type="checkbox"/> Bellows	<input type="checkbox"/> _____	
	<input type="checkbox"/> TA-air	<input type="checkbox"/> AD 2000	<input type="checkbox"/> _____	
Function	<input type="checkbox"/> Shut-off	<input type="checkbox"/> Control		
Body material	<input type="checkbox"/> _____			
Shut-off device material	<input type="checkbox"/> _____			
Lining	<input type="checkbox"/> _____			
Overall length in mm	<input type="checkbox"/> _____			
Actuation:	<input type="checkbox"/> Free shaft end	<input type="checkbox"/> Handwheel	<input type="checkbox"/> Pneumatic	<input type="checkbox"/> Electric
Electronical actuator	Brand: <input type="checkbox"/> _____			
	Nominal voltage: <input type="checkbox"/> 220 – 240V AC	<input type="checkbox"/> 380 – 460V DS	<input type="checkbox"/> 24V DC	
	Additional function: <input type="checkbox"/> _____			
Pneumatic actuator	<input type="checkbox"/> Single-acting	<input type="checkbox"/> Double-acting	<input type="checkbox"/> Spring-opening	<input type="checkbox"/> Spring-closing
	Supply air pressure: <input type="checkbox"/> _____ bar			
Actuator accessoires:				
Solenoid valve:	<input type="checkbox"/> 3/2 way valve	<input type="checkbox"/> 5/2 way valve		
Manufacturer	<input type="checkbox"/> _____			
Control voltage	<input type="checkbox"/> 24V DC	<input type="checkbox"/> 230V/50Hz AC	<input type="checkbox"/> _____	
Limit switch:	<input type="checkbox"/> Inductiv	<input type="checkbox"/> Microswitch	<input type="checkbox"/> _____	<input type="checkbox"/> Ex version
Positioner:				
Input signal:	<input type="checkbox"/> 4-20 mA	<input type="checkbox"/> 0-10V		
Analogue feedback:	<input type="checkbox"/> yes	<input type="checkbox"/> no		